

AZUD PC SYSTEM Zalecana maksymalna długość linii (m)*											
Model		CISNIENIE WEJŚCIOWE (BAR)	Odległość między emiterami (m)**								
			0,2	0,3	0,5	0,6	0,75	1	1,25	1,5	2
16	1.4L	2	87	123	186	214	253	312	366	417	510
		3	110	156	236	272	323	399	469	525	650
		4	127	179	272	313	371	460	540	615	750
	1,6 L	2	80	110	160	190	220	275	320	360	430
		3	100	140	210	240	280	350	400	460	560
		4	115	160	240	275	325	400	465	530	650
	2,2 L	2	61	87	131	152	179	228	262	300	365
		3	78	110	167	193	229	287	335	375	465
		4	89	127	192	223	264	326	385	440	540
	4L	2	42	59	89	102	122	151	178	203	248
		3	53	75	113	131	155	192	226	257	320
		4	60	89	130	152	178	221	261	296	362
AZUD PC SYSTEM Zalecana maksymalna długość linii (m)*											
Model		CISNIENIE WEJŚCIOWE (BAR)	Odległość między emiterami (m)**								
			0,20	0,30	0,50	0,60	0,75	1,00	1,25	1,50	2,00
20	2,3 L	2,0	95	134	198	228	265	325	382	420	520
		3,0	124	171	250	292	340	410	490	550	675
		4,0	141	197	292	335	391	480	562	640	780
	4L	2,0	70	96	143	165	193	235	277	314	380
		3,0	88	123	182	209	246	302	352	401	489
		4,0	101	141	210	247	284	349	406	462	566